

RIMS MTB

Model	Dimension			Weight ± 5% [g]	Riding style						Rim joint				Brake		Holes					Eyelets			Color		Valve hole		Technical data				
	Rim dimension	ERD [mm]	Outer width [mm]		Height [mm]	Road race	Touring	Cross race	Cross mountain	Enduro cross	Free ride	Carbon	Welded	Sleeve joint	Pin joint	Disc brake	Rim brake	20 holes	24 holes	28 holes	32 holes	36 holes	None	Single	Double	UD Carbon	Black	White	Presta ø 6.5 mm	Schrader ø 8.5 mm	Tire dimension	Max. tire pressure** [bar]	Recommended system weight max. [kg]
XR/X-Rims																																	
XRC 320 26	559 x 19	540	26	20	325			●			●			●				●				●				●		26" x 1.7" – 2.35"	3	100			
XRC 320 29	622 x 19	602	26	20	370			●			●			●				●				●				●		29" x 1.7" – 2.35"	3	100			
XR 400 26	559 x 18	544	23.8	17.8	400			●			●			●			●	●	●			●			●	●		26" x 1.5" – 2.25"	4	110			
XR 400 white	559 x 18	544	23.8	17.8	400			●			●			●				●	●			●		●	●	●		26" x 1.5" – 2.25"	4	110			
XR 400 29	622 x 18	606	23.8	17.8	450			●			●			●				●	●			●			●	●		29" x 1.5" – 2.25"	4	110			
X 430 26	559 x 18	545	23.8	17.8	430			●			●			●				●	●			●			●	●		26" x 1.5" – 2.25"	4	110			
X 470 29	622 x 18	606	23.8	17.8	470			●			●			●				●	●			●			●	●		29" x 1.5" – 2.25"	4	110			
XM/M-Rims																																	
XMC 350 27.5	584 x 21.5	566	28	20	370			●			●			●				●				●			●	●		27.5" x 1.9" – 2.5"	3	110			
XMC 350 29	622 x 21.5	604	28	20	395			●			●			●				●				●			●	●		29" x 1.9" – 2.5"	3	110			
XM 450 26	559 x 19.5	541	26	18.7	450			●			●			●				●	●			●			●	●		26" x 1.7" – 2.4"	4	120			
XM 490 29	622 x 19.5	603	26	18.7	500			●			●			●				●	●			●			●	●		29" x 1.7" – 2.4"	4	120			
M 480 26	559 x 19.5	541	26	18.7	470			●			●			●				●	●			●			●	●		26" x 1.7" – 2.4"	4	110			
M 480 27.5	584 x 19.5	566	26	18.7	490			●			●			●				●	●			●			●	●		27.5" x 1.7" – 2.4"	4	110			
M 520 29	622 x 19.5	604	26	18.7	520			●			●			●				●	●			●			●	●		29" x 1.7" – 2.4"	4	110			
EX/E-Rims																																	
EX 500 26	559 x 21	540	27.8	19.8	500			●			●			●				●	●			●			●	●		26" x 1.9" – 2.5"	3	130			
E 530 26	559 x 21	541	27.8	19.8	530			●			●			●				●	●			●			●	●		26" x 1.9" – 2.5"	3	130			
533d 26	559 x 22	539	27.7	20.3	520			●			●			●				●	●			●			●	●		26" x 1.9" – 2.5"	3	130			
533d 27.5	584 x 22	564	27.7	20.3	540			●			●			●				●	●			●			●	●		27.5" x 1.9" – 2.5"	3	130			
533d 29	622 x 22	602	27.7	20.3	575			●			●			●				●	●			●			●	●		29" x 1.9" – 2.5"	3	130			
FR/F-Rims																																	
FR 600 26	559 x 25	538	32	21.7	600			●			●			●				●	●			●			●	●		26" x 2.1" – 3"	3	140			
F 630 26	559 x 25	536	32.5	22	630			●			●			●				●	●			●			●	●		26" x 2.1" – 3"	3	140			